



Australasian Certification Authority for Reinforcing and Structural Steels Ltd

CERTIFICATE OF PRODUCT PERFORMANCE

Certificate Number: 170501



has satisfied the Authority that it complies with the rules of the ACRS Product Certification Scheme, and the relevant ACRS Quality and Operations Assessment Procedures. Where appropriate, and as listed below, it has further satisfied the Authority that it manufactures and/or supplies products that conform with the standards listed below, and is entitled to use the ACRS mark in relation to the products listed on this certificate.

SCOPE OF CERTIFICATION

Reinforcing Wire Manufactured in Coil to AS/NZS 4671:2001

Products listed on this Manufactured Product certificate may be relied upon as having the benefit of ACRS Product Scheme certification after any subsequent processing only where cut, or bent, or welded (e.g. into mesh, or fitments) by an ACRS Certified mesh manufacturer or reinforcing processor.

For mesh Approval, refer to the mesh manufacturer's ACRS certificate. For Approval of fitments and other processed materials, refer to the bar processor's ACRS Fabricated Product certificate.

Full details of the products for which certification has been achieved should be viewed at: www.steelcertification.com

By authority of ACRS Board:

Andrew Wheeler, Acting Executive Director

Valid until:

31 December 2022

First certified:

6 June 2017



2022 VALID TO 31 DEC



Australasian Certification Authority for Reinforcing and Structural Steels Ltd

Products assessed by ACRS to AS/NZS 4671:2001

To be read in conjunction with Certificate Number: 170501



has satisfied the Authority that it complies with the relevant ACRS Quality and Operations Assessment Procedures. Where appropriate, and as listed below, it manufactures products as indicated by " \checkmark ", below and is entitled to use the ACRS mark with these products.

Products manufactured:

AS/NZS 4671 Grade 500L Wire (nominal size)

Plain Round Wire R500L	4.0 to 10 mm	\checkmark
	3.75 mm	✓
Deformed Ribbed Wire D500L [^]	4.0 to<5.0 mm	✓
	5.0 to 11.9 mm	✓
Deformed Indented Wire I500L	4.0 to 10.0 mm	✓

[^]For use in pipe reinforcing only and shall not be used as edge wires in any reinforcing mesh sheet.

Wire Markings





Tag



